



Distributed By:
TURBEL ENTERPRISES INC.
www.turbel-enterprises.com
info@turbel-enterprises.com
049 502 1161 | 02 88230181
09189366439 | 09178517005

TASKI® Step Off

Heavy-Duty Liquid Floor Stripper

An amine type concentrated liquid stripper formulated to penetrate and re-emulsify metal interlock finishes and sealers and suspend the broken film to permit easy removal.

Key Properties

- **Heavy-Duty**
Removes old sealers and finish without destroying the floor via the 4-way stripping action: uniformly wets the surface penetrates through the finish and sealers layer emulsifies the softened finished holds the particles in suspension to prevent redeposition and permit easy removal
- **Concentrated**
Economical. Dilutable with water and can be used to selectively strip any water emulsion finish by just varying the dilution
- **Non-Ammoniated**
Leaves no unpleasant odor wherever it is applied. Very pleasant to work with
- **Biodegradable**
Environmentally Safe

Designed For

- Recommended to properly prepare all types of floors except unsealed wood before application of floor finish
- Recommended to floors with heavy wax build-up. It can readily strip Complete, Stride, Over & Under, old waxes and most other water emulsion finishes and sealers, whether they are metal complexed or not





Distributed By:
TURBEL ENTERPRISES INC.
www.turbel-enterprises.com
Info@turbel-enterprises.com
049 502 1161 | 02 88230181
09189366439 | 09178517005

TASKI® Step Off

Heavy-Duty Liquid Floor Stripper

General Usage

Mix a 1 : 4 dilution using hot water.

Note: use a 1:8 dilution with warm water for selective removal of finish from a “Technique” sealed floor. Use a green or blue pad.

Apply Liberal amounts of solution uniformly on floor with mop. If splashing occurs, wipe off surfaces with a clean rag dampened with water.

Let stripper solution soak in for 5-7 minutes. Increase soak time if using cool water. Keep areas to be stripped wet.

Scrub thoroughly using a stripping pad or brush to break-up film.

Pick-up all of the solution with a clean mop, wet vacuum or an automatic scrubber.

Thoroughly rinse floor with clear water.

Let floor dry completely before applying recommended Diversey brand floor finish or sealer.

Technical Data

Form / Color	Clear light straw-colored liquid
Fragrance	Mild
Specific Gravity	1.067 - 1.107
pH	12.0 - 13.5
Solubility	Fully miscible in water

The above data is typical of normal production and should not be taken as a specification.

Safe Handling and Storage Information

Store in original closed containers or (where applicable) in an approved bulk tank, away from sunlight and extreme temperatures. Keep away from strong bases. Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet.