



Distributed By:
DYNADVANCE TRADING AND
DISTRIBUTION (DTD) INC.
www.beyondhygiene.net
02 8252 0958 / 02 7005 8338

TASKI® Freedom

Heavy-Duty Floor Stripper

A new and innovative deep penetrating stripper that requires minimal mechanical action to properly prepare resilient floor for recoating. Taski Freedom Heavy Duty Stripper allows stripping and recoating in up to 50% less time than ordinary strippers do.

Key Properties

- Single mop agitation dissolves heavy wax build-up and even though interlock finishes. Does the job with less equipment time. Reduces electrical consumption
- Eliminates the need for neutralizing. Simply pick-up the dirty solution, a few passes with new coat of finish
- Saves 1/3 to 1/2 the time and labor versus ordinary stripping procedure
- Biodegradable, non-ammoniated and water-based

Designed For

- Specifically for floor finish removal on resilient and hard floors
- It should not be used on wood floors or painted surfaces.
- It is not recommended for use on linoleum or rubber tile floors since bleaching or softening could occur
- On asphalt tile, test first in an inconspicuous area to determine if bleaching occurs


General Usage

Prepare a 1:4 dilution of Taski Freedom with water. For best results, use hot water in diluting Taski Freedom.

Apply a solution liberally on the floor with a mop. Floor should be uniformly wet.

Soak the floor for about 4 to 5 minutes.

Agitate the floor with the same mop used in applying the product. Pick up the dirty solution completely with a mop or wet vacuum. Allow the floor to dry completely.





Distributed By:
DYNADVANCE TRADING AND
DISTRIBUTION (DTD) INC.
www.beyondhygiene.net
02 8252 0958 / 02 7005 8338

TASKI[®] Freedom

Heavy-Duty Floor Stripper

Technical Data

Form/Color	Clear colorless liquid
Fragrance	Product specific
Relative Density	1.07 (20 °C)
pH (1%)	13.0 - 14.0
Solubility	Fully miscible in water

The above data is typical of normal production and should not be taken as a specification.

Safe Handling

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet.
Only for professional users / specialists.

Storage Information

Store in original closed containers away from extremes of temperature.